

SELECTED MODEL

Luno 136 ON W TRIAC SOFT

BLACK RAL 9005

COLOR LIGHT 2700 K CRI≥ 95

INDEX 14.1101.D16.002

ΙP

IP44

WEIGHT 0,70 kg

SOURCE LIGHT LED 12.6 W

POWER SUPPLY 230V 50Hz

DIMMING RC TRIAC

FLUX

1008 LM BEAM ANGLE

>90°



Series Luno

SURFACE MOUNTED

The simplicity of the Luno suits every interior - traditional, modern, raw. These are plafonds with an integrated LED source of high quality, and colour-rendering index CRI≥95. The lack of visible mounting screws highlights the minimalism of the light fittlings, increased tightness up to IP44 allows the lamp to be installed in a bathroom. The milk aperture with a sandblasted glass structure gives a soft, pleasant, and even light, while eliminating the glare effect. Two diameter sizes and three heights of luminaire allow you to create interesting arrangements on the ceiling.

Basic, complementary and spot light. Suitable for commercial spaces such as hotels, restaurants and offices, but also as lighting for home (bathroom).

TO DOWNLOAD:

3D Luno

Declaration of Conformity Luno

Luno ON Manuals

 $\underline{\text{Warranty conditions and limitations}}$

